












NEW


<u>OEM-14</u>	OEM-14		HD-TVI StarLight bullet camera with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,8~12 mm motorized lens (103°~32,1°). ICR. OSD, ATW, AGC, BLC, HLC, WDR 120 dB, 3D-DNR, brightness, sharpness, mirror, motion detection and privacy mask. IP67. 3AXIS bracket. 12V DC.
<u>OEM-1</u>	OEM-1		HD-TVI StarLight vandal dome with Smart IR of 40 m, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 ~ 12 mm motorized lens (103°~32,1°) with autofocus. ICR filter. OSD, ATW, AGC, BLC, WDR 120 dB, 3D-DNR, brightness, sharpness, mirror, motion detection and privacy mask. IP67, IK10. 3AXIS. 12V DC.
<u>CTD-587</u>	CTD-587		Outdoor vandal Dome Day/Night IR 30m, 3 Megapixels. 1/3" CMOS Progressive Scan. 3Mp, 1080P / 720P / D1 / CIF. IR cut filter. 0.1 lux. 2.8 mm fixed lens. H.264 / MJPEG. AGC, 3D-NR, BLC, HLC, digital WDR. privacy masks. MicroSD. IP67. IK10. DC 12V.

## CCTV - DVR / XVR

NEW

Reference	Model	Photo	Description
<u>AS-88</u>	AS-88		DVR COLOSO EVOLUTION 5 in 1, 32 ch HDCVI/HDTVI/AHD/CVBS or 32 ch IP 6MP. H.265+/H.265/H.264+/H.264. 2 way audio. 16ch 1080P. 128 Mbps. Recording: 4M-N, 1080P (15 fps), 1080N, 720P, 960H, D1, CIF (25 fps). HDMI and VGA at 1080P + BNC output. IVS. facial detection. 2 HDD SATA up to 10TB. RJ45 Gigabit. Onvif, CGI, P2P, DDNS. 2 USB, 1 RS485. 12V DC. SmartPSS and Apps iDMSS/gDMSS.

## CCTV - Accesories

Reference	Model	Photo	Description
<u>CTD-254</u>	CTD-254		Hidden microphone in smoke detector