



































<u><a href="#">HYU-643</a></u>	HYU-643		Mifare 13,56 MHz card reader, vandal protection IK10. 50 mm reading range. Wiegand 26/34 communication. RS485. Suitable for outdoors.
<u><a href="#">HYU-645</a></u>	HYU-645		Fingerprint and Mifare card reader. Up to 5.000 fingerprints. Card reading range 3 to 10 cm. RS485 communication. Suitable for outdoors.

## Access Ctrl/Presence - Access / Attendance Terminal

Reference	Model	Photo	Description
<u><a href="#">HYU-731</a></u>	HYU-731		Standalone HYUNDAI Presence Control terminal with biometric fingerprint reading and EM card reader. Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records. It incorporates 2.4 "screen. TCP / IP communication. Not suitable for outdoor use.
<u><a href="#">HYU-732</a></u>	HYU-732		Standalone HYUNDAI Presence Control terminal with biometric fingerprint reading and MIFARE card reader. Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records. It incorporates 2.4" screen. TCP / IP communication. Not suitable for outdoor use.
<u><a href="#">HYU-730</a></u>	HYU-730		Standalone HYUNDAI Access Control and Presence terminal with biometric fingerprint reading and MIFARE card reader. Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records. It incorporates a 2.4 "screen. TCP / IP communication. Inputs for 1 door sensor and 1 REX output button. Outputs for 1 door lock relay and 1 doorbell relay. Not suitable for outdoor use.

## Accessories - Reader / Desktop Programmer

Reference	Model	Photo	Description
<u><a href="#">HYU-646</a></u>	HYU-646		EM and Mifare® USB card registrar. Plug&Play (without controllers). Power supply led indicator and status communication. USB power supply.